

## C-MEX EYEPIECE DIGITAL CAMERA

### **MODEL : CMEX-lite2 (DC.2000L)**

Camera with CMOS sensor for microscope's eyepiece tube of  $\varnothing 23.2\text{mm}$ . With 2.0 Mpx the CMEX camera is equipped with USB-2 data interface and supplied with Image Focus 4 software.

Besides capturing images and videos, the software allows measurements on still and live images and annotations on captured images. Compatible with Windows 7, 8 and 10, both 32 and 64 bits configurations.

Supplied with C-mount, USB 2.0 cable,  $\varnothing 30.0$  and  $\varnothing 30.5$  mm adapters for stereo microscopes, 76 x 24 mm calibration slide (1mm/100).

Compatible with Intel Core 2, 2.8 Ghz or higher, 2 GB, USB-3 port, 17 inch display

### **Technical specifications:**

**Sensor:** CMOS 1/3.2" Sony Aptina

**Resolution:** 2 Megapixels (1600x1400)

**Pixel size:** 2,8 x2,8 micras

**IR Filter:** 380-650 nm

**Exposure:** Automatic

**White balance:** Automatic

**Additional adapters:**  $\varnothing 30.0\text{mm}$ ,  $\varnothing 30.5\text{mm}$

**Calibration slide:** included

**Software:** Imagefocus Alpha

**USB port:** USB 2.0

**Compatible with Windows OS:** 7, 8, 10 (32 y 64 bits)

**Accessories included:** Cable USB de 1.4m, stereo microscopes adapters, CD Rom with software

